

SELECTABLE GALLONAGE NOZZLES

High-Range 368-Series Selectable Gallonage Nozzles

- 95-125-150-200-250 GPM (360-475-550-750-950 LPM)
- 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Foam Tube Style 215 (see page 24)



Style 368

368 High-Range Selectable Gallonage Nozzle with Pistol Grip

368-TO High-Range Selectable Gallonage Nozzle Tip Only



Style 368-TO

368-BA High-Range Selectable Gallonage Breakapart Nozzle

- Combination of Style 368-TO tip and Style 102 shutoff (see page 25)

368-BC High-Range Selectable Gallonage Nozzle with Pistol Grip

- Brass construction



Style 368-BC

368-BCTO High-Range Selectable Gallonage Nozzle Tip Only

- Brass construction

368-BI High-Range Selectable Gallonage Nozzle with Integrated 2-1/2" Inst. Male

- BIM inlet

368-TP High-Range Selectable Gallonage Nozzle Tip with Playpipe

- Combination of Style 368-TO tip and Style 130 playpipe (see page 26)



Style 368-TP

368-BCTP High-Range Selectable Gallonage Nozzle Tip with Playpipe

- Brass construction
- Combination of Style 368-BCTO tip and Style 130-BC playpipe (see page 26)

Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
368	2-1/2" (65mm)	11" (279mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-TO	1-1/2" (38mm)	7.1" (180mm)	3.2 (1.5kg)	95-125-150-200-250	360-475-550-750-950
368-BA	2-1/2" (65mm)	13" (330mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-BC	2-1/2" (65mm)	11" (280mm)	14.7 (6.7kg)	95-125-150-200-250	360-475-550-750-950
368-BCTO	1-1/2" (38mm)	7.1" (180mm)	9.9 (4.5kg)	95-125-150-200-250	360-475-550-750-950
368-BI	2-1/2" (65mm)	13.7" (350mm)	6.3 (2.8kg)	95-125-150-200-250	360-475-550-750-950
368-TP	2-1/2" (65mm)	16.8" (426mm)	9.5 (4.3kg)	95-125-150-200-250	360-475-550-750-950
368-BCTP	2-1/2" (65mm)	17" (431mm)	21 (9.5kg)	95-125-150-200-250	360-475-550-750-950

