

Dual-Purpose Ground Monitors



Style 622-1, 622-2, 622-3

- Suitable for use as a portable monitor or a deck gun with features to meet the changing demands of the fire service
- Full 3" waterway for flow rate of up to 1250 GPM (4800 LPM)
- Full 360° rotation in the deck model (Style 622-3), 180° in the portable models (Style 622-1, 622-2)
- Vertical travel of 63° from 12° to 75° above with inbuilt 37° safety stop from 18° to 55° above
- Compact folding base can be stored in any truck compartment or pre-connected in the hose bed
- Carbide-tipped spikes for extended resistance to wear
- Large handle for excellent portability
- Fully enclosed worm gear is protected from the elements
- Available in portable (Style 622-1 and 622-2) or deck-mount (Style 622-3)
- Compatible with a wide range of Protek nozzles and accessories

		Style 622-1	Style 622-2	Style 622-3		
Max. GPM(LPM)		1000 (3800) *	800 (3030)	1250 (4800)		
Inlet	Size	2-1/2" to 5"	2-1/2" (x2)	3"	4"	3"
	Type	Thread	Thread	Flange	Flange	Thread
Outlet		2-1/2"	2-1/2"	2-1/2"		
Control		Single Hand-Wheel	Single Hand-Wheel	Single Hand-Wheel		
Material		Alloy	Alloy	Alloy		
Finish		Red Powder Coating	Red Powder Coating	Red Powder Coating		
Travel	12 to 75° Vertical		12 to 75° Vertical	12 to 75° Vertical		
	180° Rotation		180° Rotation	360° Rotation		
Weight		32 lbs.	32 lbs.	27 lbs.		

* Maximum flow rate is subject to selection of inlet size

Compatible Products

Style 622-3



Style 656
The pipe



Style 656 shown with
Style 622 monitor liftoff



Style 120
Quad Stacked Tips



Style 190
Direct Mount Flange



Style 119
Stream Shaper



Style 847
Monitor Nozzle



Style 887
Self-Educting Nozzle
(500 GPM)



Style 888
Self-Educting Nozzle
(750 GPM)

sales @protekfire.com.tw • www.protekfire.com.tw